

GO-GO[®]

LX WITH CTS SUSPENSION

3 & 4-WHEEL SCOOTER

FEATURES, PERFORMANCE AND TRAVEL-READY



Comfort-Trac Suspension

The **Go-Go[®] LX with CTS Suspension** (Comfort-Trac Suspension) brings a new level of performance, features and value to travel mobility. Featuring CTS independent front and rear suspension, sleek style, feather-touch disassembly and standard lighting, the Go-Go LX with CTS Suspension is the most advanced travel product available.



Go-Go[®] LX with CTS Suspension
3-wheel



Go-Go[®] LX with CTS Suspension
4-wheel

PRIDE[®] MOBILITY SCOOTERS
LIVE YOUR BEST[®]

pridemobility.com

SPECIFICATIONS

GO-GO® LX WITH CTS SUSPENSION

3W: S50LX 4W: S54LX

Weight capacity:	300 lbs.
Maximum speed ¹ :	Up to 4.4 mph
Ground clearance ² :	1.5" at motor
Turning radius:	3W: 33" 4W: 44.75"
Overall length ² :	3W: 39.75" 4W: 41"
Overall width ² :	20.5"
Front tires:	3W: 2" x 8" solid 4W: 2" x 7" solid
Rear tires:	2.5" x 8" solid
Range per charge ^{1,4} :	3W: Up to 9.44 miles 4W: Up to 10.5 miles
Total weight without batteries ⁵ :	3W: 85.4 lbs. 4W: 87.4 lbs.
Heaviest piece when disassembled:	3W: 34 lbs. (front section) 4W: 36.6 lbs. (front section)
Standard seating:	Type: Foldable, compact, vinyl-covered molded plastic Weight: 23 lbs. Material: Black Vinyl Dimensions: Width: 17", Depth: 17"
Motor output:	24-volt DC motor, sealed mini-transaxle
Brakes:	Regenerative and electromechanical
Battery requirements ^{3,5} :	(2) 12V Deep-cycle Size: (2) 12 AH or (2) 18 AH (optional) Weight: 12 AH: 20 lbs. per battery pack, 18 AH: 33 lbs. per battery pack
Battery charger:	Off-board, 2 amp
Color:	Interchangeable Shrouds



Red



Blue

Optional



Orion Yellow



Onyx Black



Pear Pink



Sunburst Orange

- 1 Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition. These specifications can be subject to a variance of (+/- 10%).
- 2 Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).
- 3 AGM or gel cell type required.
- 4 Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
- 5 Battery weight may vary based on manufacturer.

NOTE: All specifications subject to change without notice.

The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

FEATURES

- CTS Suspension (Comfort-Trac front and rear independent suspension)
- Feather-touch disassembly permits simple frame separation with only one hand
- Pride's exclusive black, non-scuffing tires
- Auto-connecting front to rear cable
- Includes sets of easily changeable colored panels - Red and Blue
- Front frame-mounted seat post offers maximum stability
- Frame design easily disassembles into 5 super lightweight pieces for convenient transport and storage
- Modular design for easy serviceability
- Microprocessor-based controller offers optimal power management and added safety features
- Standard front tiller-mounted basket
- Charger port in tiller
- Convenient off-board dual voltage charger can charge battery pack on-board or off-board
- Optional color shroud panels: Onyx Black, Orion Yellow, Pearl Pink, Sunburst Orange

Pride® Lifts & Ramps

Compatible Lifts:

- Backpacker®
- Outlander



PRIDE® MOBILITY SCOOTERS
LIVE YOUR BEST®

(US) 800-800-8586 • (Canada) 888-570-1113

pridemobility.com